

## PARAFUSO COM SEXTAVADO INTERNO - CABEÇA CILÍNDRICA DIN 912 - AÇO LIGA - UNC/BSW - OXIDADO OLEADO



Diâmetro\* ► / Comprimento\* ▼ (POL)

#4 UNC 40	#5 UNC 40	#6 UNC 32	#8 UNC 32	#10 UNC 24	1/4 UNC 20	5/16 UNC 18	3/8 UNC 16	7/16 UNC 14	1/2 UNC 13	1/2 BSW 12	5/8 UNC 11	3/4 UNC 10	7/8 UNC 9	1 UNC 8	1-1/4 UNC 7	1-1/2 UNC 6
3/16																
1/4	1/4	1/4	1/4	1/4												
5/16	5/16	5/16		5/16												
3/8	3/8	3/8	3/8	3/8	3/8	3/8										
1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2									
		5/8	5/8	5/8	5/8	5/8	5/8									
		3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4						
			7/8	7/8	7/8	7/8	7/8		7/8	7/8						
		1	1	1	1	1	1	1	1	1	1	1				
			1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4				
			1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	1-1/2		
				1-3/4	1-3/4	1-3/4	1-3/4	1-3/4	1-3/4	1-3/4	1-3/4	1-3/4			1-3/4	
				2	2	2	2	2	2	2	2	2	2	2		
				2-1/4	2-1/4	2-1/4	2-1/4		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	
				2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2
					2-3/4	2-3/4	2-3/4		2-3/4	2-3/4	2-3/4	2-3/4	2-3/4	2-3/4		
					3	3	3	3	3	3	3	3	3	3	3	3
					3-1/4	3-1/4	3-1/4		3-1/4	3-1/4	3-1/4					
					3-1/2	3-1/2	3-1/2	3-1/2	3-1/2	3-1/2	3-1/2	3-1/2	3-1/2	3-1/2	3-1/2	3-1/2
					4	4	4		4	4	4	4	4	4	4	4
						4-1/2	4-1/2		4-1/2	4-1/2	4-1/2	4-1/2	4-1/2	4-1/2	4-1/2	4-1/2
						5	5		5	5	5	5	5	5	5	5
							5-1/2		5-1/2	5-1/2	5-1/2	5-1/2	5-1/2	5-1/2	5-1/2	5-1/2
							6		6	6	6	6	6	6	6	6
									6-1/2	6-1/2	6-1/2	6-1/2	6-1/2	6-1/2	6-1/2	6-1/2
									7	7	7	7	7	7	7	7
									8	8	8	8	8	8	8	8
										10	10	10	10	10	10	10
															12	12

\* Medidas em polegadas.

- Tabela em medidas padrão, consulte-nos para medidas especiais.