



DIN 08 B-2

ENGRENAGEM PARA CORRENTE DUPLA

- **Material:** Aço SAE 1040/* Material ferro com cubo soldado
- **Rolo:** 8,51mm
- 1/2" x 5/16"
- 12,7 x 7,75 mm
- **B1 = 7,2 / B2 = 21 / B3 = 34,9 / b1 = 7 / C = 1,3 / r3 = 13**



Z Nº Dentes	DUPLA					
	de	dp	dm	D1	A	
8	38,0	33,18	20	10	32	0,09
9	42,0	37,13	24	10	32	0,13
10	45,9	41,10	28	10	32	0,18
11	49,9	45,07	32	12	35	0,24
12	53,9	49,07	35	12	35	0,30
13	57,9	53,06	38	12	35	0,36
14	61,9	57,07	42	12	35	0,44

15	65,9	61,09	46	12	35	0,52
16	69,9	65,10	50	16	38	0,63
17	74,0	69,11	54	16	38	0,73
18	78,0	73,14	58	16	38	0,85
19	82,0	77,16	62	16	38	0,97
20	86,0	81,19	66	16	38	1,10
21	90,1	85,22	70	16	40	1,29
22	94,1	89,24	70	16	40	1,37
23	98,1	93,27	70	16	40	1,46
24	102,1	97,29	75	16	40	1,64
25	106,2	101,33	80	16	40	1,82
26	110,2	105,36	85	16	40	2,02
27	114,2	117,46	90	16	40	2,56
28	118,3	121,50	100	16	40	2,79
29	122,3	125,54	100	20	40	2,87
30	126,3	129,56	100	20	40	3,0
31	130,3	133,60	100	20	40	3,13
32	134,4	137,64	100	20	40	3,26
33	138,4	141,68	100	20	40	3,40
34	142,5	145,72	100	20	40	3,54
35	146,5	149,76	100	20	40	3,69
36	150,6	153,80	100	20	40	3,84
37	154,6	157,83	100	20	40	4,00

38	158,6	161,87	100	20	40	4,15
39	162,7	169,95	*108	20	55	5,67
40	188,6	182,07	*108	20	55	6,26
42	192,6	186,10	*108	20	55	6,39
48	200,7	184,18	*108	20	55	6,75
50	208,8	202,26	*108	20	55	7,17
57	237,1	230,54	*108	25	55	8,65
60	249,2	242,66	*108	25	55	9,35
76	313,9	307,33	*108	25	55	13,30
95			*108		55	

CNBFIX